



Preparation and Application Information

Material Name: Rocky Mountain Stone Products Repel 10

SECTION 1-PRODUCT AND COMPANY IDENTIFICATION

Product Name(s): Repel 10 Water Repellant

Rocky Mountain Stone Products
780 North 700 West
Salt Lake City, UT 84116

Emergency Contacts:

Rocky Mountain Stone Products
Tel: (801) 355-3221 (7:30am-5pm MST)

Health and Technical Contacts:

Health Issues & Technical Information (7:30am-5pm MST): (801) 355-3221
Product Information (7:30am-5pm MST): (801) 355-3221

SECTION 2-SAFETY INFORMATION

Repel 10 Water Repellent is a water carried product. Use appropriate safety equipment and job site controls during application and handling. Read the full label and MSDS for precautionary instructions before use.

FIRST AID

Ingestion: Call a physician, emergency room or poison control center immediately for instructions on properly inducing vomiting. Get Medical Assistance.

Eye Contact: Rinse thoroughly for 15 minutes. Get immediate medical assistance.

Skin Contact: Remove contaminated clothing and rinse thoroughly for 15 minutes. Seek medical assistance if persistent irritation develops. Launder contaminated clothing before reuse.

Inhalation: Seek medical attention if irritation develops.



Preparation and Application Information

Material Name: Rocky Mountain Stone Products Repel 10

SECTION 3-PREPARATION

Protect people, vehicles, property, plants, windows and all non-masonry surfaces from product, splash, residue, fumes, and wind drift. Protects and/or divert foot and auto traffic.

Thoroughly clean the surface. Clean newly constructed and repointed surfaces before application. Repel 10 will not impair adhesion of most sealing and caulking compounds. Always test of compatibility.

Though Repel 10 may be applied to slightly damp surfaces, best performance is achieved on clean, visibly dry and absorbent surfaces. Excessive moisture inhibits penetration, reducing the service life and performance of the treatment.

Protect window glass before use of Repel 10. Masking is effective protection for use with this product. If protecting windows is impractical follow these steps:

1. Clean window glass thoroughly before application to nearby concrete or masonry.
2. Do not use in wind or when air or surface temperatures are hotter than 95°F.
3. Try to keep Repel 10 off the glass.
4. After treated surfaces have to be protected from water for 6 hours. If product is on window glass, clean as soon as possible with soap and warm water. Remove all dried residue within 3-5 days.

SURFACE AND AIR TEMPERATURES

Best surface and air temperatures are 40-95°F during use and for 8 hours after. If freezing conditions exist before application, let masonry thaw. The water carrier may freeze at low temperatures or evaporate in high temperatures. Both conditions impair penetration and results. Clean up is more difficult from surfaces hotter than 95°F.

EQUIPMENT

Apply with brush, roller, or low pressure spray (<50psi). Fan tips are recommended for sprayers. Avoid atomization of material.

STORAGE AND HANDLING

Store in a cool, dry place. Always seal container after dispensing. Do not alter or mix with other chemicals. Published shelf life assumes upright storage of factory sealed containers in a dry place. Maintain temperatures of 45-100°F. Keep from freezing. Do not double stack pallets. Dispose of unused product and container in accordance with local, state, and federal regulations.



Preparation and Application Information

Material Name: Rocky Mountain Stone Products Repel 10

SECTION 4-APPLICATION

Before Use, read, "Preparation" and "Safety Information"

ALWAYS TEST

Always test each type of surface before overall application for suitability and results. Test using the following application instructions. Let test area dry thoroughly before inspection.

DILUTION

Do Not Dilute Or Alter

VERTICAL APPLICATION INSTRUCTIONS

For best results, apply "wet on wet" to a visibly dry and absorbent surface.

1. Spray: Saturate from the bottom up, creating a 4-8" (15-20cm) rundown below the spray contact point. Let the first application penetrate for 5-10min. Re-saturate. Less will be needed for second application. Brush or broom out heavy runs and drips that do not penetrate.
2. Brush or Roller: Saturate uniformly. Let penetrate for 5-10 min. Re-saturate. Less will be needed for second application. Brush or broom out heavy runs and drips that do not penetrate.

HORIZONTAL APPLICATION INSTRUCTIONS

Saturate in a single application. Use enough to keep the surfaces wet for 2-3 minutes before penetration. Broom out puddles until they soak in.

DENSE SURFACE APPLICATION INSTRUCTIONS

Apply in a single coat. Use enough to completely wet the surface without creating drips, puddles, or rundown. Do not over apply. Test for Application rate.

Treated surfaces dry to touch in 1 hour. Protect surfaces from rainfall for 6 hours following treatment. Protect for foot and vehicle traffic until visibly dry. Repel 10 gains its water repellency properties in 72 hours.

CLEANUP

Clean tools, equipment and overspray with soap and warm water.